



2003 HUMMER H1



4-DOOR WAGON



4-DOOR OPEN TOP

## COMPONENTS & FEATURES

**ENGINE:** V8, 6.5L Turbocharged diesel, electronically controlled

**HORSEPOWER (SAE hp):** (est.) 195 @ 3400 rpm

**TORQUE (lb.-ft./Nm):** (est.) 430 lb.-ft. @ 1800 rpm

**TRANSMISSION:** 4L80-E 4-speed automatic

**DRIVETRAIN:** Full-time 4WD with TorqTrac® 4 (TT4) traction system

**TRANSFER CASE:** New Venture Gear model 242

**GEARED HUBS:** Gear ratio of 1.92:1

**DIFFERENTIAL:** Zexel Torsen® III torque biasing differential

**STEERING:** Power-assisted

**BRAKES:** Hydro-Boost 4-wheel in-board mounted Meritor-WABCO ABS power disc brakes

**SUSPENSION:** Independent double-A frame with open-end coil springs and hydraulic shock absorbers

**FRAME:** Steel box section with five cross members

## SPECIFICATIONS & PERFORMANCE DATA

### HEIGHT:

4-DOOR OPEN TOP: 77 in.

4-DOOR WAGON: 75 in.

**WIDTH (WITHOUT MIRRORS):** 86.5 in.

**LENGTH:** 184.5 in. (NOTE 1)

**WHEELBASE:** 130 in.

**TRACK WIDTH:** 71.6 in.

**GROUND CLEARANCE:** 16 in.

**APPROACH ANGLE:** 72° (NOTE 1)

**DEPARTURE ANGLE:** 37.5°

**MAXIMUM TOWED LOAD:** (NOTE 2)

4-DOOR OPEN TOP: 7,867 lb.

4-DOOR WAGON: 7,409 lb.

**RUN-FLAT CAPABILITY:** 20 miles @ 30 mph (NOTE 3)

**TURNING RADIUS:** 26.5 ft.

**FUEL CAPACITY:** 25 gal. tank plus 17 gal. auxiliary tank

For more information check out [www.HUMMER.com](http://www.HUMMER.com) or call us at 1 800 REAL 4WD.

## STANDARD EXTERIOR EQUIPMENT

6061 T6 hardened aircraft aluminum body

Composite hood

Heavy-duty steel bumper towing shackles

3/16 in. rocker panel protection constructed from T6 aluminum

Tonneau cover for Open Top (Black or Tan)

Vertical rear doors (Wagon)

The heavy-duty straight brush guard

Drivetrain protection

Trailer towing unit with wiring harness

Halogen headlights

Heated power mirrors

## STANDARD INTERIOR EQUIPMENT

Cloud Gray cloth interior

Remote Keyless Entry

Power windows (Express-Down for driver)

Lighted visors (Wagon only)

Deluxe rearview mirror with compass, thermometer and auto dimmer

Monsoon™ 12-disc CD changer and cassette player

3-point safety belts

Air conditioning with auxiliary rear unit

Air inflation line with quick connects

E-Z Kool® glass (windshield, passenger, driver windows)

Privacy glass (Wagon rear windows only)

Heated windshield

Tachometer

CTIS controls and in-dash tire pressure gauges

Cruise control

## WHEELS & TIRES

17 in. one-piece cast-aluminum wheels

37 x 12.5R-17 load range "E" Goodyear Wrangler GSA radial

Central Tire Inflation System (CTIS) with on-board air compressor

Tire bead retaining system

Run-flat tire system (NOTE 3)

Concealed air delivery system

## OPTIONAL EQUIPMENT

Cloud Gray leather-trimmed seats (heated front seats)

Eaton® Electronic ELocker™ locking rear differential

17 in. two-piece forged aluminum wheels with dual beadlocks and run-flats

featuring a fully concealed air delivery system to support CTIS

37 x 12.5R-17 load range "E" Goodyear Wrangler MT/R tire with DuraWall™

puncture resistance technology

12,000 lb. winch

## EXTERIOR COLORS




Black



Bright White



Black Diamond Metallic



Competition Yellow



Ocean Blue Metallic



Firehouse Red



Metallic Pewter



Summit Silver



Woodland Green

**HUMMER**® LIKE NOTHING ELSE.™

NOTE 1: The data on this page applies to models without winch and optional accessories. Models with winch are impacted as follows: PAYLOAD: Decrease by 137 lbs.; CURB WEIGHT: Increase by 137 lbs.; LENGTH: Increase by 6 in.; APPROACH ANGLE: Decrease by 25°. NOTE 2: Maximum towing capacity will vary based on vehicle loading. Gross Combination Weight (GCW) of vehicle and trailer cannot exceed 15,300 lbs. for highway use only. A weight-carrying hitch gives your vehicle the capability to tow a maximum weight of 7,500 lbs. A weight-distributing hitch with spring bars may give your vehicle the capability to tow a maximum weight of up to 7,867 lbs., depending on model and payload. These are not necessarily weights the vehicle will tow at sustained highway speeds or varying altitudes. Maximum trailer weight ratings are calculated assuming a base vehicle, except for option(s) necessary to achieve the rating, plus driver. The weight of other optional equipment, passengers and cargo will reduce the maximum trailer weight your vehicle can tow. NOTE: The maximum allowable weight your vehicle can tow off-road, no matter what type of hitch is being used, is 5,000 lbs. See your HUMMER dealer for additional details. NOTE 3: For emergency use only, a "get home" capability that will cause tire damage. Consult your local HUMMER dealer for availability of accessories and current specifications. All specifications are based on latest information available at time of printing. Manufacturer reserves the right to make changes, at any time and without notice, in prices, colors, materials, equipment, specifications, models and availability. Details and specs may vary according to local regulations and conditions. LIKE NOTHING ELSE is a trademark of General Motors Corp. HUMMER and the vehicle's grille are registered trademarks of General Motors Corp. TorqTrac (TT4/ABS) is a registered trademark of AM General Corp. Eaton is a registered trademark of Eaton Corp. ELocker is a trademark of Eaton. Durawall is a trademark of Goodyear. Zexel Torsen is a trademark of Torsen. Monsoon is a trademark of Monsoon, Inc. E-Z Kool is a trademark of Pilkington. © 2003, General Motors Corporation.